## **Billet Mounting Brackets**

Our patented quick-release billet mounting brackets are accepted by most race-sanctioning bodies and clubs. Flat surface mounts and dual clamp roll bar mounts combine with band clamps for 2.5 lb. fire extinguishers. Band clamps for 1.0 and 1.4 lb. fire extinguishers combine with flat surface mounts and single clamp roll bar mounts. Note: Clamps and mounts must be used together. First, choose the correct band clamp size, then choose a flat surface or a roll bar mount. One year limited warranty.



Billet Mounting	For 1.0/1.4 lb fire ext.		For 2.5 lb fire ext.	
Accessory	Brushed	Polished	Brushed	Polished
Fire ext. band clamp	BB100B	BB100P	BB250B	BB250P
Flat surface mount	BMF01B	BMF01P	BMF01B	BMF01P
1½ in. Roll bar mount	BMR00B	BMR00P	BMR10B	BMR10P
15/8 in. Roll bar mount	BMR01B	BMR01P	BMR11B	BMR11P
13/4 in. Roll bar mount	BMR02B	BMR02P	BMR12B	BMR12P
2 in. Roll bar mount	BMR13B	BMR03P	BMR13B	BMR13P
21/4 in. Roll bar mount	BMR04B	BMR14P	BMR14B	BMR14P

## **Extreme Duty Mounting Brackets**

Speed is critical when deploying a fire extinguisher. Count on our patented Extreme Duty quick-release brackets to allow fast action while withstanding rigorous use. These NHRA accepted fiberglass-reinforced nylon brackets are designed to meet MIL-STD-810G and withstand inertia loads in excess of 27G. Made for extreme duty, they offer an exceptional mounting solution for off road and racing enthusiasts. One year limited warranty.





Description*	Part Number
Flat surface mount for 2.5 lb fire extinguishers	NB300
Flat surface mount for 5.0 lb fire extinguishers	NB425
15/8 in. Roll bar mount for 2.5 lb fire extinguishers	NBR301
15/8 in. Roll bar mount for 5.0 lb fire extinguishers	NBR401
13/4 in. Roll bar mount for 2.5 lb fire extinguishers	NBR302
13/4 in. Roll bar mount for 5.0 lb fire extinguishers	NBR402

<sup>\*</sup>Designed for use with H3R Performance fire extinguishers.

#### Universal Fire Extinguisher Seat Mounts

Our fully adjustable NHRA accepted fire extinguisher seat mount installs easily in most vehicles, attaching to the seat rail bolts or above the slider of the driver or front passenger seats.\* Not only does this put the extinguisher at your fingertips but it avoids the need to drill mounting holes into your vehicle. Available in black or brushed finishes, this patented mount accepts all H3R Performance fire extinguisher billet aluminum, Extreme Duty and standard brackets. Made in the U.S.A. One year limited warranty.



## (800) 249-4289 www.h3rperformance.com

Distributed by:





# HalGuard **Premium Clean Agent Fire Protection**




























HG500C





Model	HG100B/C/R*	HG250B/C/R*	HG500B/C/R*	HG1100R	HG1550R
Extinguishing Agent	Halotron® 1				
USCG Approved	No	No	Yes	Yes	Yes
Agent Weight	1.4 lb.	2.5 lb.	5.0 lb.	11.0 lb.	15.5 lb.
Gross Weight	2.6 lb.	5.4 lb.	8.8 lb.	22.5 lb.	27.5 lb.
UL Rating	1B:C	2B:C	5B:C	1A:10B:C	2A:10B:C
Height	10.0 in.	14.8 in.	15.3 in.	21.9 in.	21.9 in.
Width	3.6 in.	5.0 in.	6.0 in.	8.5 in.	8.5 in.
Diameter (Depth)	2.6 in.	3.0 in.	4.3 in.	6.0 in.	6.0 in.



\* Available finishes: B - Black powder coat; C - Chrome-plated; R - Red powder coat





MX100B











В	MX500C	N

Model	MX100B/C/R*	MX250B/C/R*	MX500B/C/R*
Extinguishing Agent	Sodium bicarbonate	Monoammonium phosphate	Monoammonium phosphate
USCG Approved	No	Yes	Yes
Agent Weight	1.0 lb.	2.5 lb.	5.0 lb.
Gross Weight	2.2 lb.	5.0 lb.	8.8 lb.
UL Rating	2B:C	1A:10B:C	3A:40B:C
Height	10.0 in.	14.8 in.	15.3 in.
Width	3.6 in.	4.5 in.	7.25 in.
Diameter	2.6 in.	3.0 in.	4.3 in.

<sup>\*</sup> Available finishes: B - Black powder coat; C - Chrome-plated; R - Red powder coat

MaxOut™ rechargeable dry chemical fire extinguishers effectively smother flammable liquid fires without conducting electricity back to the operator – just the type of protection needed in an automotive environment (never use water on a flammable liquid or electrical fire). MaxOut™ extinguishers containing more than 1 lb. of agent are also rated for common combustibles like wood, paper, rubber, and some plastics. This added effectiveness makes them ideal for marine and home use as well. High quality steel cylinders and all-metal valve construction. Six year limited warranty. UL listed and rated.

